



CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) Descriptions of corner evidence searched for involved many corners. Except for the brass cap at the SW corner of the Section and the two spikes in the pavement (at the NW corner and the SW corner) all corners used were original stones found in place.

> DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the northeast corner of subject Section 11 we set a standered of breaks..... cap monument in a mound of stone on a steep south slope near the summit of a bare hill 3/4 mile east of the junction of Hwy 37 and U.S.93 No bearing trees in limits.

The corners set as shown on reverse were set by specified procedures, double proportionate distances and single proportionate distances. Angulation was measured with a one second Wild theodolite.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE OTHER SIDE

J.W. Ninneman

Surveyor's Seal	I. J.W. Ninneman	
	certify that the information shown herein is true and	. N.
MONTANA	Signature of Ground Party Chief	See other side.
JACK W. MINISTEMAN	J.W. Ninneman	Sec. 11
0 m. co co	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	Twp: 36 M. R. 27 W
FOIL FER & LAID	J.W. Mineman Signature of Surveyor	= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln 19......, was noted on the cross-index plat and is This "corner record" was filed for record on the 11th day of March ELEANOR L. VAUGHN, assigned page No....., in book No.....,

Cross Index No. E-17 T.

534 ES Registration Number

County Official

DIAGRAM OF CORNER:

FORM 125 - 41483