CERTIFIED CORNER RECORDATION 15&22 36N **P.M., MT** Corner Sec. County 1893 G.L.O. Original Record by Peter McCardell et. al.: Set a limestone, 14X12X5 ins., 10 ins. in the I. ground for 1/4 sec. cor. mkd. "1/4" on the N. face. Established one bearing tree: A fir, 14 ins. diam., bears \$38°30'E, 100 lks. dist., mkd. "1/4 \$ BT" Raised a mound of earth 1 1/2 ft. high, 3 1/2 ft. base alongside. 1977 B.L.M. Remonumentaton Record by Larry A Christiansen: The 1/4 sec. cor. of secs. 15 and 22, monumented with a limestone, 14x12x5 ins., firmly set, 10 ins. in the ground, mkd. as described in the original record, with a mound of stone, 4 ft. base, 1 1/2 ft. high, to the N., and witnessed by the remains of the original bearing trees. At the corner position, set a 2 1/2 in. diam. aluminum post, 22 ins. in the ground, with the cap mkd. as shown: T36N R27W 1977 Established one new bearing tree: A fir, 14 ins. diam., bears S49 1/2°E, 169 lks. dist., mkd. "1/4 S22 BT". Bury the original stone alongside and raise a flat mound of stone, 3 ft. diam., around the iron post. II. Found a 2 1/2 in. diam. aluminum pipe, firmly set, protruding 4 ins. above the ground, with a 3 1/4 in. diam. B.L.M. brass cap mkd. as shown above. from which: A rotten stump, bears S38°E, 66.0 ft. dist., with axe marks. (GLO-record) A fir, 21 ins. diam., bears S49°E, 111.5 ft. dist., mkd. with visible scribe. (BLM-record) A fir, 9 ins. diam., bears \$19°W, 51.5 ft. dist., mkd. with a healed face. III. Painted bearing trees and attached Land Survey Monument and Bearing Tree signs. Magnetic Declination: 20° East. 04/23/97 Reg. No.: 9008LS ployer: U.S. FOREST SERVICE SKETCH OF CORNER LINCOLN . This "corner record" was filed for record Office of Clerk and Recorder, County of JULY 31.1997 was noted on the cross-index plat and is assigned page No. CORAL M.CUMMINGS

in book No.

County Officia

27W

corner this sheet