INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated.
- 2. Description of evidence of the corner corners.

 3. Description of monument and accessories set to perpetuate the corner position.


 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

CERTIFIED CORNER RECORDATION

__ T. <u>36 N., R. 27 W. P.M.M. Lincoln</u> County Corner __ CN 1/16, Sec. 30

- 1994 Certificate of Survey No. 5111 by Dawn Marquardt, Reg. No. 7328S: "Set 5/8 in. x 24 in. rebar with plastic cap stamped 7328S."
- II. Found a 5/8 in. dia. rebar with 1 in. dia. plastic cap marked Marquardt 7328S, bears S30°56'20"E, 0.5 ft. from calculated position.
- III. At the accepted rebar position, set a 3/4 in. diam. by 30 ins. long aluminum rod, 27 ins. in the ground with 3 1/4 in. diam., U.S.D.A., Forest Service aluminum cap, marked as shown:



from which


A fir, 7 ins. diam., bears S27 $^{\circ}$ E, 19.7 ft. dist., mkd. CN 1/16 S30 BT. A fir, 11 ins. diam., bears S21 $^{\circ}$ W, 43.3 ft. dist., mkd. CN 1/16 S30 BT.

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

Set a 6 ft. galvanized steel guard post with Land Survey Marker & Property Boundary decals, West. 4.8 ft.

Magnetic Declination: 20° East





CERTIFICATION Thomas Hommel

Ronald A. Pearson

certify that this Corner Record correctly represents work performed compliance with the

/6/95 Reg. No. 9008LS U.S. FOREST SERVICE

LINCOLN Office of Clerk and Recorder, County of _ . This "corner AUG21,1997 record" was filed for record on ___ 9934was noted on the cross-index plat and is assigned page No. CORAL M.CUMMINGS book No. . County Official

· - corner this sheet

T. 36N R. 27W PMM