

## INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner 1/4 Cor. Secs. 20 & 29 T. 36 N. R. 27 W. P.M.M. Lincoln County

- I. 1903 original G.L.O. record by Abraham L. Rinearson & Gordon C. Smith: Set stone and marked two bearing trees.


1970 remonumentation B.L.M. record by Joseph E. French: "The 1/4 sec. cor. of secs. 20 and 29, monumented with a porphyry stone, 15 x 10 x 6 ins. firmly set, mkd. 1/4 on the N. face, and witnessed by the remains of the original bearing trees:

A stump hole, bears S42 1/4° W. 122 lks. dist., with a fallen fir, 12 ins. diam., mkd. 1/4 S29 lying alongside.

A fir, 8 ins. diam., bears N63 1/4° W. 15 lks. dist., mkd. 1/4 S20 BT.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



from which a new bearing tree:

A fir, 6 ins. diam., bears S5 1/2° W. 21 lks. dist., mkd. 1/4 S29 BT.

- II. Found a 2 1/2 ins. diam. iron pipe, 6 ins. out of ground with 3 1/4 ins. diam. B.L.M. brass cap marked as shown above, from which

A fir, 7 ins. diam., bears S5° W. 13.8 ft. (21 lks.) dist., healed face.

A fir, 9 ins. diam., bears N63° W. 10.3 ft. (16 lks.) dist., healed face

- III. Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

Magnetic Declination: 20° East



SKETCH OF CORNER

## CERTIFICATION

Rex Rice

I, Rex O. Rice certify the information shown herein is true and correct.

Signature Ground Party Chief

Ronald A. Pearson

I, Ronald A. Pearson certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Signature of Surveyor & Seal


Date: 11/13/95 Reg. No. 9008LS

Employer: U.S. FOREST SERVICE

Office of Clerk and Recorder, County of LINCOLN. This "corner record" was filed for record on AUG21,1997 was noted on the cross-index plat and is assigned page No. 9959 in book No. CORAL M. CUMMINGS County Official By OLB

Cross Index No. R-07 T. 36N R. 27W P.M.M.

Sec. 20



• - corner this sheet