Original and/or subsequent record used to evaluate the corner position

Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

escription of monument and accessories set to perpetuate the corner position.

Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

T. <u>36N.</u> R. <u>28W.</u> P.M.M. _ Sec. 3 C. C. Lincoln

I. From original 1894 G.L.O. notes. Set Basalt Stone 16"x12"x6", 11" in ground for Closing Corner of Sections 3 & 4, marked C.C. on South with 3 grooves on East & West faces, from which:

A Pine 20" in diam. bears S.60°45'W., 63 lks.

A Fir 6" in diam. bears S.44°E., 18 lks. (SEE NOTE I-A)

Found Brass cap on iron pipe, B.L.M. II.

Found Pine snag, 20" bears S.60°45'W., 41.6 ft.

Found Stump hole, bears S.44°E., 11.9 ft.

Found 8" Pine, bears \$25%°E., 36.97 ft.

Found 6" Red Fir, bears S.75% W., 14.52 ft.

- III. Set rock cairn around Mon.
- I-A. B.L.M. re-mon., June, 1969: Set 21/2" I.P. w/Brass cap, 24" in ground. S.3 B.T., 8" Pine, bears S.25%°E., 56 lks. S.4 B.T., 6" Fir, bears S.751/2°W., 22 lks.



· - corner this sheet

CERTIFICATION certify the information shown herein is true and correct. Signature Ground Party Chief Carl R. McMillen, L.S. certify that this Corner Record correctly represents work performed SNAG Date 12/15/83 Reg. No. 4659-S Employer: Carl R. McMillen & Assoc. SKETCH OF CORNER Sec. ろ C.C., Lincoln Office of Clerk and Recorder, County of _ __ . This "corner __ day of 198≰ was noted on the cross-index plat and is assigned page No. __ Janet BF Siegel by Betty County Cificial book No.

A-13 T. 36N. H. 28W. PMM