INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- corners.

 3. Description of monument and accessories set to perpetuate the corner position.

 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
- 5. Certification must be signed and seared by negative 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner _____ 1/4 Sec. 4/3 T. 36 N. R. 28 W. PMM Lincolm

From original 1894 G.L.O. notes. Set Basalt Stone 15"x11"x6", 12" in ground I. marked 1/4 on West face, from which:

A 5" Fir bears S.49°45'W., 22 1ks.

A 10" Fir bears S.12%°E., 20 lks.

(SEE NOTE I-A)

- II. Found Brass cap on iron pipe, B.L.M. Found 6" Red Fir, bears S.48°E., 49.50 ft. Found 14" Red Fir, bears N.35°W., 16.50 ft.
- III. Placed rock cairn around Mon.
- B.L.M. re-mon., July 1969: Set 21/2" I.P. w/Brass cap, 8" in ground. I-A. S.3 B.T., 6" Fir, bears S.48°E., 75 lks. S.4 B.T., 14" Fir, bears N.35°W., 25 lks.



SURVEYON ZED FIR CERTIFICATION F. D. Higgins certify the information shown herein is true and correct. Signature Cround Party Chief Carl R. McMillen, L.S certify that this Corner Record correctly represents work performed Date: 12/15/83_{Reg. No.} 4659-S Employer: Carl R. McMillen & Assoc. SKETCH OF CORNER Sec. Office of Clerk and Recorder, County of ___ Lincoln _ . This "corner march 21 record" was filed for record on the ___ day of 19*8*4 was noted on the cross-index plat and is assigned page No. <u>3552</u> Janet BF Sliegel by Betty County Official book No. _ C-13 T. 36N.R. 28W. PMM · corner this sheet