

INSTRUCTIONS

1. Original and/or recent record used to evaluate the corner position.
2. Description of monument found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Sec. 17, 18, 19 & 20 T. 37N R. 26W P.M.M. Lincoln County

Original Record:


Set a limestone 14x12x9 ins. 10 ins. in the ground with 3 notches on South and 5 notches on East edges.

Dug pits and raised mounds.

Found original stone buried in large rock pile.

Set aluminum cap on top of stone.

See C. of S. Nos. 1648 and 1666 for adjacent corners



SKETCH OF CORNER

CERTIFICATION

I, Dawn McAlister

certify the information shown herein is true and correct.

Dawn McAlister
Signature Ground Party Chief

I, D.K. Marquardt

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

D.K. Marquardt
Signature of Surveyor & Seal

Date: 9-9-88 Reg. No. 2989ES


Employer: _____

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the Sept 12 day of 1988 was noted on the cross-index plat and is assigned page No. 3906 in book No. _____

Grant BF Sugil by Deed
County Official

Cross Index No. N-5 T. 37N R. 26W PMM

Sec. 18



• - corner this sheet