Corner: CS 1/16	Sec. 1 Twp. 37 N., R. 27 W., P.M.M.	Lincoln County Montana
Record :	NONE	
Found Evidence	: NONE	
Perpetuation :	Set a 5/8 inch diameter Rebar with a 1 Ked 4975-S for corner. From which: A 11.3 inch DBH Douglas Fir scribed C	
	9.6 ft distance	
	A 13.8 inch DBH Douglas Fir scribed CS 1/16 S 1 BT Bears S 70° W 12 ft distance	
B _ 10 41 40 5	Painted red bands and attached warning	ng and bearing tree signs to both
Declination 18°1 Douglas Fire 13°/ 08H Douglas fire Douglas fire	CS 1/8 S1 BT	CERTIFICATION Curify the Information shown helpful is true and correct Signature of Ground Party Chief Care A that this Conse is correctly epresents work performed by a brunder my direction in compliance with the "Corner Recordation DAVIS Signature of Subveyor & Seal 275-5 Signature of Subveyor & Seal 275-5 Supply in Davis Subveyor & Seal 275-5 Supply in Davis Subveyor in Linc.
Sketch of Corner	المراث	Section
This "corner record" was	rder, County of AMCON. If filed for record on	
Cross Index No. Tw	p. N., R. W., P.M.M. • THIS CORNER	[-+- ● -+- -] •

CERTIFIED CORNER RECORDATION