

CERTIFIED CORNER RECORDATION

Corner: CS 1/16 Sec. 1 Twp. 37 N., R. 27 W., P.M.M.

Lincoln County Montana

Record : NONE

Found Evidence : NONE

Perpetuation : Set a 5/8 inch diameter Rebar with a 1 1/4 inch plastic cap stamped Ked 4975-S for corner.

From which:

**A 11.3 inch DBH Douglas Fir scribed CS 1/16 S1 BT Bears N 19° W
9.6 ft distance**

**A 13.8 inch DBH Douglas Fir scribed CS 1/16 S 1 BT Bears S 70° W
12 ft distance**

Painted red bands and attached warning and bearing tree signs to both

Declination 18 °E

A diagram showing a tree limb with a cut labeled "5/8 KED". The limb is divided into two sections. The upper section is labeled "Douglas Fir" and "11 3/4 DBH". The lower section is labeled "Douglas fir" and "13 0 DBH". The cut is made at an angle of 57° to the horizontal. The limb is supported by a vertical post labeled "6 1/2\"/>

C 5 1/6 S1BT

CS 1/6 51 BT

CERTIFICATION

1. George Clark
certify the information shown herein is true and correct

Signature of Ground Party Chief

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation

(7022-ED) (MISD) (MECA)
DAVIS

Signature of Surveyor & Seal

Date: 6/20/2017 Reg. No. 10000000000000000000
Employer: Davis Surveying, Inc.

SURVE


Sketch of Corner

Office of Clerk and Recorder, County of Lincoln.

This "corner record" was filed for record on 10/31/01 **10541**
was noted on the cross-index plat and is assigned page No. _____

In book No. _____ Coral M. Cummings by DB
County Official

Section



Cross Index No. Twp. N., R. W., P.M.M. ● THIS CORNER