

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

I find no evidence of original corner. Corner set by single proportion.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

I set a $1\frac{1}{2}$ " I.D. x 30" Iron Pipe 28" in ground with brass cap marked per sketch below. Date of work: Oct. 1973

New RM as follows:

RM - Sec. 20 - 12" Douglas Fir N. 50° E., 35.50 feet
RM - Sec. 29 - 6" Douglas Fir S. 7° W., 30.80 feet

All measurements to center of tree.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal

I, _____
certify that the information shown herein is true and correct.


Signature of Ground Party Chief

I, J. T. SHAW
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

23435
Registration Number

DIAGRAM OF CORNER:



= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln
This "corner record" was filed for record on the 14th day of February, 1974, was noted on the cross-index plat and is assigned page No. 324, in book No. 1
Edward L. Vaughn, Jr. By: Mae Watson, Deputy
County Official