

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

I find no evidence of corner but find two bearing tree stumps and one bearing tree lying on ground.

Record: Set a Limestone 16" x 14" x 4"
 A Pine 14" bears South 24° East, 111 links
 A Pine 16" bears South 77°-20' West, 133 links
 A Pine 26" bears North 22°-30' West, 98 links

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Oct. 1973

I set a 1½" I.D. x 30" galvanized iron pipe with brass cap marked per sketch below.

Declination 22° East.

I made new RM as follows:

RM - Sec. 28 - 8" P. Pine bears North 62° East, 34.20 feet
 RM - Sec. 29 - 6" P. Pine bears North 50° West, 20.0 feet
 RM - Sec. 32 - 10" P. Pine bears South 27° West 39.45 feet
 RM - Sec. 33 - 10" P. Pine bears South 21°/East, 23.0 feet
 30'

All measurements to center of trees.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
 (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal


I, _____
 certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, J. T. Shaw
 certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

J. T. Shaw
 Signature of Surveyor

DIAGRAM OF CORNER:



= Corner recorded on the sheet

2343-S
 Registration Number

Office of Clerk and Recorder, County of Lincoln
 This "corner record" was filed for record on the 4th day of February, 1974, was noted on the cross-index plat and is assigned page No. 325, in book No. 1
 Eleanor L. Chugh, Mac Watson, Deputy
 County Official