

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

I find a bearing tree stump.

(Record: A pine 9" bears North 34° East 186 links.)

I find a fire scarred stump.

(Record: A pine 24" bears North $62^{\circ}-30'$ West .52 links.)

From the 9 inch pine stump I measure original bearing and distance and find after digging some rotten wood standing vertical in ground. Measure from fire scarred stump and hit edge of same hole.

Record: Set a post 3 feet long 3 inches square 24 inches in ground.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Oct. 1973

I set a $1\frac{1}{2}$ " I.D. x 30" galvanized iron pipe with brass cap 28 inches in ground marked per sketch below.

Make new RM as follows:

RM - Sec. 29 - 12 inch P. Pine bears North 61° West 99.75 feet.

RM - Sec. 28 - 12 inch P. Pine bears North 30° East 44.30 feet.

All measurements to center of tree

Declination 22° East.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

N

I drove $5/8$ " x 36" rebar through 9" bearing tree stump into ground and signed stump.

Surveyor's Seal

I, _____
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, J. T. Shaw
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

J. T. Shaw


Signature of Surveyor

2343-S

Registration Number

DIAGRAM OF CORNER:

N.



= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of February 1974, was noted on the cross-index plat and is assigned page No. 226, in book No. 1

Eleanor L. Coughlin, Mae Watson, Deputy

County Official