

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

I find no evidence of original corner but find a fence corner and a charred stump with blaze that fits bearing tree description.

Record: Set a Quartzite boulder 15" x 11" x 7" in ground.
A Pine 15" bears South 12° West 12 links

I re-establish $\frac{1}{4}$ corner from bearing tree stump.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Oct. 1973

I set a $1\frac{1}{2}$ " I.D. x 30" galvanized iron pipe 24 inches in ground with brass cap stamped per sketch below,

I make new RM as follows:

RM - Sec. 28 - 12" P. Pine North 53° East 53.0 feet
RM - Sec. 33 - 12" P. Pine South 26° West 50.30 feet

All measurements to center of tree.

Declination 22° East.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal

I, _____
certify that the information shown herein is true and correct.


Signature of Ground Party Chief

I, J. T. Shaw
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

J. T. Shaw

Signature of Surveyor

DIAGRAM OF CORNER:



= Corner recorded on the sheet

2343-S
Registration Number

Office of Clerk and Recorder, County of *Lincoln*
This "corner record" was filed for record on the *4th* day of *February* 19*74*, was noted on the cross-index plat and is assigned page No. *327*, in book No. *1*

Charles L. Hughes *MacWatson, Deputy*
County Official