quent record used to evaluate the corner position

2. Description of evidence found, note discrenancies in the record, state method of establishing lost or obliterated

3. Description of monument and accessories set to perpetuate the corner position

Sketch or corner, show all pertinent data which can best be shown in a sketch example, topography ties, position of accessories, etc.
Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

T. ___37N. R. __28W. P.M.M. Lincoln W. 1/4 Sec. 14 Corner

I. From original 1894 G.L.O. notes: Set a post 3' long, 3" square, marked 1/4 on West face, from which:

A Tamarack 16" in diam. bears N.35°30'W., 26 lks.

A Tamarack 8" in diam. bears N.23°15'E., 37 lks.

(SEE NOTE I-A)

II. Found 1969 B.L.M. Brass capped Mon. Found 12" Tamarack stump, bears N.23°15'E., 24.42 ft., visible scribing. Found 16" Tamarack stump (appears to be Pine), bears N.35°30'W., 17.16 ft., visible scribing.

Found 8" Tamarack, bears N.48°W., 12.54 ft.

Found 6" Red Fir, bears S.75°E., 25.08 ft.

III. Put rock cairn around Mon.

book No.

B.L.M. re-mon., August, 1968: Set 21/2" I.P. w/Brass cap, 24" in ground. I-A. S.14 B.T., 5" Fir, bears S.75°E., 38 lks. S.15 B.T., 7" Larch, bears N.48°W., 19 lks.



8'' Higgins McMillen, BLM Date: 12/14/83_{Reg. No.} 4659-S Employer: Carl R. McMillen & Assoc SKETCH OF CORNER Sec. incoln Office of Clerk and Recorder, County of _ march 215t record" was filed for record on the ___ _ day of 19*8*4 was noted on the cross-index plat and is assigned page No. <u>3563</u>

Janet BF Siegel by Betty County Official

L-17 T. 37N . R. 28W . PMM

· corner this sheet