- ent record used to evaluate the corner position
- Description of evidence found, note discrepancies in the record, state method of establishing is
- escription of monument and accessories set to perpetuate the corner position.
- Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
 Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
 Fill in Cross Index & Seciton Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

N. 1/4 Sec. 14 T. <u>37N•</u> R. <u>28W•</u> P.M.M. <u>Lincoln</u>

- I. From original 1894 G.L.O. notes: Set a post 3' long, 3" square, marked 1/4 S on North face, from which:
 - A 30" Yellow Pine bears N.35°W., 72 lks.
 - A 6" Fir bears S.26°45'W., 49 1ks.

(SEE NOTE I-A)

- II. Found B.L.M. Brass cap on iron pipe. Found 8" Red Fir, bears S.32°E., 17.82 ft.
- III. Placed rock cairn around Mon. Scribed 6" Tamarack, bears S.43°E., 37.60 ft., marked 1/4 S14 B.T., with "X" cut in tree below tag.
- B.L.M. re-mon., August, 1968: Set 21/2" I.P. w/Brass cap, 24" in ground. I-A. S.11 B.T., 6" Fir, bears N.32°E., 27 lks. S.14 B.T., 6" Fir, bears S.81°E., 84 lks.



SKETCH OF CORNER

CERTIFICATION
F. D. Higgins
certify the information shown herein is true and correct.
Z.D. Higgs
Signature Ground Party Chief
L.S. Carl R. McMillen, L.S.
certify that this Corner Record correctly represents work performed
by me or under by direction in compliance with the "Corner Recordation Act" (70-22-00) et e.g. M.B.A.)
Contraction of the second
Signature of Surveyor & Seal
Date: 12/14/83 _{Reg. No.} 4659£S
Employer: Carl R. McMillen & Assoc.

S'RED FIR Office of Clerk and Recorder, County of march 215t record" was filed for record on the _ was noted on the cross-index plat and is assigned page No. <u>2564</u> Janet BF Sugal by Beth County Official book No. .

J-19 T. 37N. R. 28W. PMM

corner this sheet