3. Description of monument and accessories set to perpetuate the corner position

- Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
  Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
- 6. Fill in Cross Index & Secitor Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

T 37N. R 28W. P.M.M Lincoln E. 1/4 Sec. 23

From original G.L.O. notes: Set a Sandstone 16"x8"x6", 11" in ground, marked I. 1/4 on West face, from which:

A Fir 16" in diam. bears S.46°15'E., 18 lks.

A Fir 7" in diam. bears N.77°15'W., 50 lks.

(SEE NOTE I-A)

Found B.L.M. Brass cap on iron pipe. II.

Found 12" Red Fir, bears N.84 3/4°E., 32.34 ft.

Found 20" Fir stump, bears S.46°15'E., 11.88 ft.

Found 16" Red Fir, bears N.77 1/4°W., 33.00 ft., visible scribing.

- Placed rock cairn around Mon. III.
- B.L.M. re-mon., June, 1969: Set 21/2" I.P. w/Brass cap, 24" in ground. I-A. S.23 B.T., 14" Fir, bears N.774°W., 50 lks. S.24 B.T., 12 " Fir, bears N. 84 3/4°E., 49 1ks.



**SKETCH OF CORNER** 

CERTIFICATION Higgins R. McMillen, 12/15/83<sub>Reg. No.</sub> 4659-S Employer: Carl R. McMillen & Assoc

P-21 T. 37N. R. 28W. PMM

Lincoln \_\_ . This "corner Office of Clerk and Recorder, County of \_ march ZIST. record" was filed for record on the \_ day of 1984 was noted on the cross-index plat and is assigned page No. 2577Sanet BF Singel by Better County Official book No. .