## INSTRUCTIONS

- ent record used to evaluate the corner position
- cription of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

3. Description of monument and accessories set to perpetuate the corner position

- Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
  Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner S.E. Cor. Sec. 26 T. 37N. R. 28W. P.M.M. Lincoln

- From original 1894 G.L.O. notes: Set a post 4! long, 4" square, with marked I. stone 12" in ground, from which:
  - A 9" Cottonwood bears N.58 3/4°E., 18 lks.
  - A 7" Cottonwood bears S.70 3/4°W., 22 lks.
  - A.8" Cottonwood bears N.67 3/4°W., 22 lks. (SEE NOTE I-A)
- II. Found C.O.E. Brass Cap set in concrete flush with ground. Found stump hole with parts of Cottonwood with scribing visible, bears S.70°45'W., 14.5 ft.
- III. Placed Rock Cairn around Mon.
  - Set 22" Tamarack bears N.22°E., 7.6 ft., not scribed due to wire and fence brace attached.
  - Set 8" Fir bears S.44°E., 106.5 ft., mkd. T37N R28W S36 B.T.
  - Set 8" Fir bears S.79°W., 58.5 ft., mkd. T37N R28W S35 B.T.
  - Set 8" Fir bears N.35 1/2°W., 80 ft., mkd. T37N R28W S26 B.T.
- I-A. C.O.E. re-mon., 1969: Set I.P. w/Brass cap. S.35 B.T., 30" Pine, bears S.594°W., 37 lks.



· - corner this sheet

