quent record used to evaluate the corner position

2. Description of evidence found, note discrepancies in the record, state method of establishing jost or obliterated

G. Description of monument and accessories set to perpetuate the corner position. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and scaled by Registered Land Surveyor in State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

T. 37N. R. 28W. P.M.M. Lincoln E. 1/4 Sec. 27

From original 1894 G.L.O. notes: Set a Sandstone 12"x8"x6", 8" in ground, mkd. I. 1/4 on West Face, from which:

A Tamarack, 10" diam., bears N.7°W., 14 lks.

- A Tamarack, 30" diam., bears \$34°30'E., 46 lks. · (SEE NOTE I-A)
- II. Found B.L.M. Brass Cap on iron pipe. Found 8" Red Fir bears N.57 1/2°E., 20.46 ft. Found 30" Tamarack stump bears S.34°30'E., 30.4 ft. Found 16" Tamarack bears N.7°W., 9.24 ft.
- III. Placed rock cairn around Mon.
- B.L.M. re-mon., June, 1969: Set 21/2" I.P. w/Brass cap, 24" in ground. I-A. S.26 B.T., 7" Fir, bears N.57%°E., 31 lks. S.27 B.T., 16" Larch, bears N.7°W., 14 lks.



🗘 16" LARCH CERTIFICATION F. D. Higgins McMillen. BLIN BLASS CAP Dai 12/12/83 Reg. No. 4659-S @30 TAMARACK Employer: Carl R. McMillen & Assoc. SKETCH OF CORNER STUMP

Office of Clerk and Recorder, County of This "corner	Sec. 27
200 $0.6t$	
record" was filed for record on the	
was noted on the cross-index plat and is assigned page No, in	
book No <u>Const BF Siegel, by Betty L. Conces</u>	
Cross Index No. T-17 T. 37N R. 28W PMM	• - corner this sheet

· - corner this sheet