
INSTRUCTIONS



- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 4 Boyd Hill Cemetary (Sec.23) 37 N., Lincoln Corner . _County

- 1954 U. S. F. S. Survey record by G. Shultz and J. Francis: As per drawing attached to U. S. F. S. Special Use Permit dated 8/18/54.
- II. Found a 1 1/2 in. diam. iron pipe, 40 ins. long, 12 ins. above ground.

A fir, 10 ins. diam., bears S 24 E, 8.5 ft. dist., mkd. with a healed face. (Origin unknown)

. III. At the position of the found iron pipe, I set in its place a 2 1/2 in. diam by 30 ins. long aluminum pipe 20 ins. in the ground, with a 3 1/4 in. diam. aluminum cap mkd. as shown.



Establish one new bearing tree:

A pine, 6 ins. diam., bears S 17 W, 28.6 ft. dist., mkd. X BT.

Painted a red band around bearing trees and attached Land Survey Monument and Bearing Tree signs.

Set a 6 ft. galvanized steel guard post with Property Boundary and Land Survey Monument decals attached. nearby.

Magnetic Declination: 20 East.



CERTIFICATION Ν Jeff Hintz certify the information shown berein is true and correct. Signature Ground Party Chief Ronald A. Pearson certify that this Corner Record correctly represents work performed by me or under my direction in compilance with the "Corner Recordanon Act" (70-22-101, et seq. M.C.A.) Tra Signature of Surveyor & Seal U.S. FOREST SERVICE SKETCH OF CORNER LINCOLN Sec. 23 _ . This ''corner Office of Clerk and Recorder, County of ___ AUG21,1997 record" was filed for record on _____ 9927 was noted on the cross-index plat and is assigned page No. CORAL M.CUMMINGS County Official book No. -Q.18 T.37N R.31W PMM · - corner this sheet Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors